

DVI CAT-5 MS Extreme Extender EXT-DVI- CAT5-MS DVI KVM Extender Gefen



Extend DVI up to
300 feet over CAT-5

DVI CAT-5 MS Extreme Extender Extends DVI up to 300 feet over two CAT-5 cables.

The DVI CAT-5 MS Extreme extends your DVI display up to 300 feet away from your DVI or HDMI™ source using cost effective CAT-5 cables.

How It Works

The DVI CAT-5 Extreme sender unit sits next to your computer, DVD player or any set-top box. The cable supplied with the DVI CAT-5 MS Extreme connects your DVI source to the sender. The DVI CAT-5 MS Extreme receiver sits next to your DVI display - up to 300 feet away. The display plugs into the back of the DVI CAT-5 MS Extreme receiver. Two CAT-5e cables connect the sender and the receiver units to each other.

Note: The DVI CAT-5 MS Extreme is fully HDCP compliant.

Features:

- * Improved compensation for cable skew
- * Uses CAT-5e cable for DDC and control signals
- * Extends any DVI (digital visual interface) compliant device up to 300 feet from the computer
- * 300 ft extension at 1280x1024/1080i
- * 150 ft extension at 1920x1200/1080p
- * Saves space on your desktop and increases productivity
- * Eliminates computer noise where you work
- * Supports VESA Standard resolutions and HDTV resolution
- * Supports DDWG standard for DVI compliant monitors
- * Installs in minutes

Specifications:

- * Video Amplifier Bandwidth: 165 MHz
- * Single Link Range: 1080P/1920 x 1200
- * Input Video Signal: 1.2 volts p-p
- * Input DDC Signal: 5 volts p-p (TTL)
- * Input/Output DVI Connector: DVI-I (29 pin) female (Digital Only)
- * Link Connector: RJ-45
- * Power Supply: 5V DC
- * Power Consumption: 20 Watts (max)
- * Dimensions: 3.4"D x 3.25"W x 1.25"H
- * Shipping Weight: 3 Lbs.

Package Includes:

- * One DVI CAT-5 Extreme-S
- * One DVI CAT-5 MS Extreme-R
- * One 6 foot DVI cable
- * Two 5V Power Supplies
- * User's Manual

Kontakt Daten - Anfrage:

Tel: 02822 33 33 990

E-Mail: info@bellequip.at

Internet: www.bellequip.at

Lösungen für

IT, EDV, Rechenzentren, Industrie, Automation, Telekommunikation, Leitstand, Rundfunk, Fernsehen, Werbung		Physikalischer Schutz – Datenschutz IT- Sicherheitsräume
19 Zoll Einbaukonsolen 2 Port KVM Switches 4 Port KVM Switches 8 Port KVM Switches 16 Port KVM Switches KVM over IP Switches Matrix KVM over IP Switches KVM Switches DVI KVM Switches DVI Matrix Switches KVM Extender KVM over IP Extender USB Extender VGA Extender VGA + Audio Extender VGA + Audio + RS232 Extender DVI Extender DVI KVM Extender HDMI Extender DVI Splitter VGA Splitter VGA Video Switches Digital Signage Audio over IP Desktop over IP Line Interaktive USV Anlagen	1p / 1p Online USV Anlagen 3p / 1p Online USV Anlagen 3p / 3p Online USV Anlagen USV Anlagen USV Batterien USV Elektro Verteilung USV Service & Support USV Software USV Anlagen für Rechenzentren ATS Automatic Transfer Switches Konverter CATx Patchkabel LWL Patchkabel Netzwerkschränke Serverschränke Remote I/O Kontakte über IP Remote Power Management Rack Monitoring / Serverraum Überwachung Wireless Communication Mobiles Ethernet / Netzwerk GSM / GPRS / EDGE / UMTS / HSDPA Device Server Secure Console Server Serielle Server USB over IP	Brandfrüherkennung Brandmelder Brandschutzpaneele Brandschutztüren Brandmeldezentralen Doppelboden / Doppelböden E-Installationstechnik Gaslöschanlagen Hochverfügbarkeitsraum / Hochverfügbarkeitsräume Kabeldurchführungen Klimageräte Leckagenwarnsysteme Netzersatzanlagen Präzisionsklimaschränke Sauerstoffreduzierung Serversafes Sicherheitsfolien Switchbox Videoüberwachung Zutrittssysteme